DRIVE CHAIN TOOL SET						
No. MCCU14	Number	▼kg 2.2 ∰ 1				
Main body	1					
Outer Bolt	1					
Inner Bolt	1					
Handle	1					
For cutter pin 4050	1	40 and 50 series cutting				
For cutter guide 4050	1	40 and 50 series cutting				
For cutter pin 60	1	60 series cutting				
For press fit plate 40	1	Press fitting type 40 series				
For 52	1	Press fitting type 52 series				
For 50	1	Press fitting type 50 (530) series				
For 60	1	Press fitting type 60 series				
Press Fit Caulking Receival Plate 1		For press fitting in all sizes / Caulking receiver				
Caulking pin	1	Caulking all sizes				
Metal Case	1	L270×W145×H32				



This model supercedes the CAU13, 11.

Usage

- For motorcycle drive chain replacements.
- For removing chain pin, press fitting joint plates (including clip type), and caulking joint pins.

Application

● For chain sizes: 420 · 428 · 520 · 525 · 50 (530) · 532 · 630 · 632

Characteristics

- This tool can be used for most domestic motorcycles.
 Based on strength analysis, the design is in an optimum shape for durability and lightness that even professionals will approve.
- Highly durable cutter pin & caulk pin is made from heat-treated special steel (SK type).
 These parts have been designed to facilitate workflow.
- Bolt removal is not required as cutter pins can be replaced from the front of the inner
- The cutter pin can be used frequently in 40 and 50 series.
 Press fitting is designed for all sizes (press fitting caulk receiving plate), and as it can also be used in caulking, this allows for a much smoother operation.
 The inner bolt does not need to be set after the joint pin has been removed as the plate press fitting uses the same outer bolt.

 The grip and handle are designed so that strength may be applied easily.
- *A drive tool such as a separate 3/8"sq. ratchet tool is required when using this tool.

DRIVE CHAIN TOOL SET





■Replacement Parts

No.	Product	89	
MCCU-BA	Outer Bolt	1	
-BB	Inner Bolt	1	
-H	Handle	1	
-CA	For cutter pin 4050	1	
-CG	For cutter guide 4050	1	
-CB	For cutter pin 60	1	
-PA	For press fit plate 40	1	
-PB	For press fit plate 52	1	
-PC	For press fit plate 50	1	
-PD	For press fit plate 60	1	
-PT	Press Fit Caulking Receival Plate	1	
-KA	Caulking pin	1	

VALVE SPRING COMPRESSOR No. MCVU5 **▼**kg 1.4 L290~420×H172 Body Attachment MCVU-A16, A20, A24, A28

*The attachment can also be used for a valve spring compressor (VSU4).

No.	Part Name	D ₁	D ₂	l	₩	
MCVU-A16	Attachment ø16.5	17	19	50	1	
-A20	Attachment ø20	20	22	50	1	
-A24	Attachment ø24	24	26	50	1	
-A28	Attachment ø28	28	31	50	1	

*The attachment can also be used for a valve spring compressor (VSU4).




This model supercedes the VSU4.

PurposeSPECIAL TOOL FOR MAINTENANCE ON INTAKE & EXHAUST VALVE

- (REMOVING/INSTALLING VAL VE SPRING) OF 4 CYCLE ENGINE.

 Guide Attachment of 4 sizes (ø16.5, 20, 24, 28) covers most types of motorcycles.
- Guide Attachment can be replaced by one-touch and wide opening for smooth operation on valve cotter





VALVE SPRING COMPRESSOR

Ð

(33)

0

Caulking pir For cutter pin 4050

For press fit plate 40

For press fit plate 50 For press fit plate 60

(OIO)

